

LED High Intensity Warning Lights



ECE R65 Approved



			@12v	@24v	Waterproof	Weight
200cd (amber) 200cd (red) 100cd (blue) 200cd (white)	120/min	quad flash	400mA (1.5A Peak)	200mA (750mA Peak)	IP67	370gms

Features:

Surface mount or bracket mount quad flash LED directional

- Intensely bright 3rd generation LEDs
- Dual voltage 12/24V (10 – 30Vdc)
- Multiple beacons may be connected together to provide synchronous or alternate flash pattern
- Bracket mount version adjusts horizontally and vertically
- Ultra low power consumption
- Integral electronics – no need for separate power pack or control unit
- IP67 rated
- 3 year guarantee

Certified to EMC directive 95/54

CE – complies with EMC Directive 89/336/EEC.

Certified to ECE R65 (amber and blue)

Certified to PIO ACS 5.

High voltage transient and polarity reversal protection fitted

Operating temperature: –30°C to +55°C (–30°C lower limit subject to intermittent and non-continuous use at temperatures below –20°C).



Applications:

Suitable for many vehicle applications including fleet, cars delivery, refuse trucks, large vehicles, road maintenance, recovery, utilities and road safety.

Materials:

Polycarbonate lens, Aluminium base coated black.

